

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Customer No.	026418	
Attorney's Docket No.:	GK-ZEI-3140 / 500343.20141	
U.S. Application No.:		
International Application No.:	PCT/EP01/01663	
International Filing Date:	FEBRUARY 15, 2001	15 FEBRUARY 2001
Priority Date Claimed:	FEBRUARY 22, 2000	22 FEBRUARY 2000
Title of Invention:	METHOD AND SYSTEM FOR DETECTING THE LIGHT COMING FROM A SAMPLE	
Applicant(s) for (DO/EO/US):	Reinhard JANKA, Volker JUENGEL, Tilo JANKOWSKI and Frank HECHT	

SUBSTITUTE  
SPECIFICATION  
and  
ABSTRACT

Docket No.: GK-ZEI-3140/500343.20141

METHOD AND SYSTEM FOR DETECTING THE LIGHT  
COMING FROM A SAMPLE

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority of International Application  
 No. PCT/EP01/01663, filed February 15, 2001 and German Application  
 No. 100 08 594.6, filed February 22, 2000, the complete disclosures of which are  
 10 hereby incorporated by reference.

BACKGROUND OF THE INVENTION

Fluorescence correlation spectroscopy (FCS) implemented in a  
 microscope construction (FCM) has proven successful for investigating  
 15 biomolecular interactions particularly where the investigations are carried out in  
 very small ranges of concentration of less than 1  $\mu\text{mol}$  and in measurement volumes  
 of less than  $10^{-14}\text{l}$ . The measurement location plays only a minor role, provided the  
 specimens to be examined are homogeneous. However, in connection with  
 structured specimens such as biological cells, knowledge and selection of the  
 20 measurement location is critically important. Formerly, this knowledge of the  
 measurement location was gained by conventional transmitted-light and incident-  
 light microscopy. For this purpose, switching was carried out between the FCS  
 detection unit and a conventional fluorescence microscope arrangement. The use of  
 conventional microscopy has several disadvantages. On the one hand, the specimens  
 25 are exposed to high radiation loading; on the other hand, the optimal measurement  
 location can not be localized in three-dimensional coordinate systems with the  
 required accuracy of less than 1  $\mu\text{m}$ .

The arrangements and methods described and claimed below, with  
 reference to the drawings, advantageously make it possible to expand the FCS  
 30 method to an imaging method (S-FCM). In this way, information can be gained  
 concerning the spatial distribution of the molecular interactions under investigation.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

Fig. 1 is a schematic block diagram of an embodiment of the  
5 invention; and

Fig. 2 is a further embodiment of the invention in schematic block  
representation.

## DESCRIPTION OF THE PRFERRED EMBODIMENTS

10 Figure 1 shows a first advantageous arrangement. With a microscope  
unit MU (in this case, an inverted microscope for observing a specimen P via an  
objective O arranged below the specimen and a tube lens TL, the specimen P being  
located on a table T which is displaceable in x-, y- and z-direction), light from a  
laser light source LLS with one or more wavelengths is focused by a scanning unit  
15 SU in a specimen either directly or through a light-conducting fiber LF via  
collimating optics KO and a primary beam splitter STPS. The scanner S allows the  
light beam to be deflected in x-direction and y-direction; different specimen layers  
can be detected through vertical adjustment of the specimen table T or of objective  
O. The light coming from the specimen passes through the scanner S again and is  
20 assigned to detection channels DES1...N by means of the secondary beam splitter  
STSS 1...N and converted into electrical signals for evaluation via a control unit CU  
in a computer. The measured signals are used to obtain image information. By  
means of a beam switching unit BS, e.g., of a fully reflecting mirror or partially  
transmitting mirror which can be swiveled in and out, light LLF from a laser light  
25 source with one or more wavelengths is focused in the specimen by means of an  
FCS unit FU via a primary beam splitter STPF.

The light sources LLS and LLF may also be identical and can be  
coupled into the units SU and FU by suitable deflecting and switching elements.  
The fluorescent light coming from the specimen is directed through secondary beam  
30 splitters STSF 1...N into one or more FCS detection channels DEF 1...N and, for

purposes of evaluation, converted into electrical signals and sent to the control unit CU. The signals are used for FCS analysis.

Autocorrelation analyses or cross-correlation analyses can be carried out depending on the detection channels that are installed. In this connection, for  
5 example, diffusion times, particle numbers, lifetimes and proportions of components are determined at the installed detection channels.

Data acquisition is controlled for both detection units by the same control unit CU and a computer C with a suitable program. Control of the specimen  
table T, vertical adjustment of the objective O and beam switching unit BS is also  
10 carried out by this computer-controlled control unit. Accordingly, as a result of integrating an FCS detection unit in a confocal laser scanning microscope system, it is also possible to combine FCS analysis results of measurements at various specimen locations to form images. This results in an advantageous arrangement which is suitable for determining FCS measurement locations with great accuracy  
15 while protecting the specimen and also for using FCS analysis results of measurements at different locations for generating images.

It is advantageously possible, for example, to use different colors to generate a color two-dimensional or three-dimensional depiction of diffusion times or other analysis results, depending on the measurement location.

20 Further, through the use of storage allocation, the recorded FCS image can be combined graphically, e.g., as an added color, with LSM images of different colors per channel.

FCS/LSM differentiating elements or quotient-forming elements or other combinations can also be formed and represented.

25 Modification, according to the invention, of the laser scanning microscope and operative combination with the FCS device unit are carried out by suitable programs in the computer by means of a device control unit shared by all of the components. The scanning unit, FCS unit, microscope unit and specimen position system are mechanically, optically and electronically adapted to one another  
30 and combined.

After the specimen is scanned, image points can be marked, brought into the measurement position for the FCS unit and measured.

The relevant points can be selected automatically according to given criteria (e.g., raster, structure detection of the image) or by the user according to individual assessment of the image recorded by the scanning unit.

The suggested construction makes possible a deliberate selection of microscopically small measurement locations in the specimen to be investigated by the FCS method. Further, it is possible to graphically detect and depict the spatial variation of the FCS analysis results from a systematic sequence of FCS measurements images and to correlate them with the LSM image.

Figure 2 shows another advantageous arrangement. In this case, a shared laser unit LLSF and a shared primary beam splitter STPFS are provided in or at a shared unit SFU. Separate beam splitters and detectors DEF, STSF and DES, STSS are shown for LSM detection and FCS detection. The detectors DEF and DES can advantageously be identically constructed. The measurement mode and evaluating mode can be selected by means of the control unit CU. The common localization of the LSM and FCS detection channels in one unit results in an advantageous arrangement. As in the construction which was described with reference to Figure 1, laser light of one or more wavelengths is focused through a scanning unit in the specimen by means of collimating optics and the primary beam splitter. A special advantage of this construction is that the measurement location for FCS measurement can also be selected by means of the scanner. In particular, it is possible in this way to advantageously expand the FCS analysis method to an imaging method (scanning FCM: S-FCSM). Reflected light and fluorescent light are captured by the objective, pass again through the scanner and are deflected by one or more secondary beam splitters into one or more LSM detection channels or FCS detection channels. Separation can then be carried out according to spectral characteristics or polarization characteristics. The detected light induces electrical signals which are directed to the control unit connected to the computer, including a suitable program, and are used in the latter for FCS analysis or image reconstruction.

In this case, the laser scanning microscope is modified in such a way that it contains components and evaluating procedures which also make it possible to carry out FCS measurements. Scan components and FCS components are combined, according to the invention, in such a way that beam splitting or beam switching such as is shown in Figure 1 can be dispensed with. The advantage of this arrangement consists in that no specimen movements are necessary for carrying out the FCS analyses at the previously selected points because the measurement location can be adjusted by means of the scanner and through vertical adjustment of the objective.

The effective connection of the operating modes is carried out in that either the scanner is stopped directly during the scanning process and an FCS evaluation is carried out at the specimen points set in this way or, after the scanning process, an FCS evaluation is carried out by adjusting the mirrors or displacing the table while the scanner mirrors are stopped at determined points. The arrangement according to Figure 2 enables FCS measurements with high positioning accuracy in quick succession. This suggested construction comprises a scanning fluorescence correlation microscope (S-FCM) which can show structural as well as biochemical information in images according to the invention.

While the foregoing description and drawings represent the present invention, it will be obvious to those skilled in the art that various changes may be made therein without departing from the true spirit and scope of the present invention.